




## EcoTender 450




## EcoTender 980



## EcoTender 1600



## EcoTender 2600



<b>Volume</b>	450 liters	980 liters	1.600 liters	2.600 liters
<b>Dimensions (l x w x h)</b>	740 x 1160 x 1150	1340 x 1160 x 1150	2040 x 1160 x 1150	2040 x 1160 x 1700
<b>Weight (empty)</b>	260 kg	350 kg	460 kg	600 kg
<b>Stackable (transportation)</b>	Yes, 1x 450 liters	Yes, 1x 980 liters	Yes, 1x 1600 liters	Yes, 1x 2600 liters
<b>Certification (diesel)<sup>(1)</sup></b>	UN ADR 6.5	UN ADR 6.5	UN ADR 6.5	UN ADR 6.5
<b>Certification (AdBlue®)</b>	-	-	-	-
<b>Material inner tank diesel<sup>(2)</sup></b>	LLDPE - black	LLDPE - black	LLDPE - black	LLDPE - black
<b>Material inner tank AdBlue®</b>	LLDPE - white	LLDPE - white	LLDPE - white	LLDPE - white
<b>Material drip tray</b>	S235JR	S235JR	S235JR	S235JR
<b>Material frame</b>	Galvanized	Galvanized	Galvanized	Galvanized
<b>Lifting points</b>	4 lifting points, always use 4!	4 lifting points, always use 4!	4 lifting points, always use 4!	4 lifting points, always use 4!
<b>Available pump sets diesel</b>	- K2 hand pump - 230V/56L - 12/24V-30-50L	- K2 hand pump - 230V/56L - 12/24V-30-50L	- K2 hand pump - 230V/56L - 12/24V-30-50L	- K2 hand pump - 230V/56L - 12/24V-30-50L
<b>Available pump sets AdBlue®<sup>(3)</sup></b>	- Hand pump - 230V/56L - 12V-30 - 24V-30	- Hand pump - 230V/56L - 12V-30 - 24V-30	- Hand pump - 230V/56L - 12V-30 - 24V-30	- Hand pump - 230V/56L - 12V-30 - 24V-30
<b>Connections diesel</b>	- Filling point + venting - Content gauge (standard) - 1" suction tube - 2" spare socket - 4x generator connection - Inspection opening Ø130mm	- Filling point + venting - Content gauge (standard) - 1" suction tube - 2" spare socket - 4x generator connection - Inspection opening Ø130mm - Grenswertgeber	- Filling point + venting - Content gauge (standard) - 1" suction tube - 2" spare socket - 4x generator connection - Inspection opening Ø130mm - Grenswertgeber	- Filling point + venting - Content gauge (standard) - 1" suction tube - 2" spare socket - 4x generator connection - Inspection opening Ø130mm - Grenswertgeber

(1) ADR certification process is yet to be completed.

(2) Material thickness depends on ADR type approval.

(3) AdBlue® pump sets are yet to be developed.